

Express Combo Trailer

Introducing the Express Combo trailer – an industrial trailer approved by the DOT, designed to cater to the needs of construction and oil field worksites and camps. With a 500-gallon tank for water supply, a 20 kW generator, and a 26 8 light tower, this trailer ensures a steady provision of water, electricity, and illumination. Plus, a 240-gallon fuel tank ensures the generator can run for up to 300 hours.

Worried about freezing temperatures? Opt for the optional freeze protection module to safeguard all water components. Rest assured, all water elements in this trailer meet potable water standards.

The Express Combo Trailer isn't just a generator, light, or water trailer. It's all three rolled into one super useful package.

Features

- DOT trailer with surge brakes; constructed of 7 channel iron
- 500 Gallon water tank with 5 GPM, 45 PSI water pump and pressure tank
- 240 Gallon fuel tank for up to 300 hours operation
- Allmand Maxi-lite II
 20 kW V-Series generator
- 320 hydraulically raised light tower with 4- 320 watt LED fixtures
- Isuzu 4LE2T, Tier 4 Final, 40.2 hp



Express Combo Trailer

Trailer Specifications

Weight (empty)	5,240 lb
Weight (full)	11,500 lb
GVWR	14,000 lb
Tandem Slipper Spring Axles	7,000 lb Axles/8,000 lb Springs
Tires	235/80R16
Surge Brakes Actuator	20,000 lb, 2 5/16" ball or 3" Ring
Length	228"
Width	83"
Transport/Extended Height	110" (transport), 27' (extended)
Trailer Frame	7" Channel Iron with Recessed Lights
Water Tank	500 Gallons (black)
Diesel Tank	240 Gallons
Water System	Flojet 5 GPM, 110 V, 45 PSI
Pressure Tank	Two-Gallon Tank for Constant Pressure

Allmand Maxi-Lite II 20kW V/Series

Engine	Isuzu 4LE2T, Tier 4 Final, 40.2 hp
Generator	20 kW single-phase 120/240V generator
Starting	12V electric; pre-heat cold starting system
Lighting	4-320 watt LED fixtures
Electrical	Alternator (generator): 60 Hz, (ML 2015kW, 1-phase) Circuits: hard-wired electrical 1-60 AMP - main disconnect 2-20 AMP/120V Duplex 3-30 AMP/240V/4-wire Twist Lock 2-50 AMP/240V/RV Outlet