

RELOCATABLE BULK LIQUID STORAGE

# DOUBLE CONE STORAGE TRAILER

RELOCATABLE · 5,000 &amp; 6,000 GALLON

Bulk cone-bottom storage that follows your operation. Stage thousands of gallons of water, fertilizer, or process liquid right where you need it; then move that capacity to the next site when the job changes. All the volume of a fixed tank, none of the permanence.



*\*Images shown may include optional features. Actual product appearance may vary based on selected configurations.*

**5,000** GAL

Two 2,500-gallon cone-bottom tanks

21 ft long · approx. 2,600 lb dry

CUSTDBLCONE2600

**6,000** GAL

Two 3,000-gallon cone-bottom tanks

21 ft long · approx. 2,800 lb dry

CUSTDBLCONE2800

## HOW THE RELOCATABLE SYSTEM WORKS

1

**TOW EMPTY**

Travels light on 3,500-lb spindle axles and a 20,000-lb clevis hitch.

2

**LOWER & FILL**

Hand-pump hydraulic ram sets the cone tanks on the ground to fill and store.

3

**RAISE & RELOCATE**

When empty, raise the unit and move full storage capacity to the next site.

## WHY CREWS CHOOSE IT

**100% DRAINING 15° CONE**

Every gallon flows out – no settling or manual sump cleanout. Liquids won't stratify between uses.

**LIGHT, LEGAL TRANSPORT**

Carries empty on standard running gear; the lift does the heavy work once you're on site.

**CONFIGURE TO YOUR LIQUID**

2" or 3" Banjo poly pump, Honda GX160 or GX200 power, optional DOT road lights.

**RIBBED-WALL™ TANKS, 10-YR WARRANTY**

Molded ribbing resists bulging; reinforced roof stands up to weather and load.

**FIELD-READY FRAME**

Powder-coated 6"×2" tube frame with built-in hose storage brackets and full hose drainage.

**TWO CAPACITIES, ONE PLATFORM**

5,000 or 6,000 gallons of relocatable storage on a common, proven chassis.

# SIDE-BY-SIDE SPECIFICATIONS

| SPECIFICATION                                    | 5,000 GAL · CUSTDBLCONE2600                  | 6,000 GAL · CUSTDBLCONE2800 |
|--|--|-----------------------------|
| <b>TANKS &amp; CAPACITY</b>                      |  |                             |
| TANK CONFIGURATION                               | Two 2,500-gal cone-bottom                    | Two 3,000-gal cone-bottom   |
| TOTAL CAPACITY                                   | 5,000 gallons                                | 6,000 gallons               |
| TANK CONSTRUCTION                                | 15° cone, Ribbed-Wall™ poly, reinforced roof |                             |
| DRAINAGE   | 100% draining cone bottom                    |                             |
| TANK WARRANTY                                    | 10-year Ribbed-Wall™                         |                             |
| <b>TRAILER &amp; RUNNING GEAR</b>                |  |                             |
| LENGTH   | 21 ft  |                             |
| WIDTH  | 100 in                                       |                             |
| HEIGHT (RAISED / LOWERED)                        | 158 in / 146 in                              |                             |
| LIFT SYSTEM                                      | Hand-pump hydraulic ram (center-pull)        |                             |
| FRAME  | 6"×2" rectangular tube, powder-coated        |                             |
| AXLES  | 2 × 3,500 lb spindle                         |                             |
| TIRES / WHEELS                                   | 235/80 R16 10-ply hwy on ag wheel            |                             |
| HITCH  | 20,000 lb clevis                             |                             |
| APPROX. DRY WEIGHT                               | ~2,600 lb                                    | ~2,800 lb                   |
| <b>PUMP, POWER &amp; PLUMBING (CONFIGURABLE)</b> |  |                             |
| PUMP   | 2" or 3" Banjo® centrifugal poly             |                             |
| ENGINE   | Honda® GX160 5.5 HP or GX200 6.5 HP          |                             |
| MANIFOLD   | 3" feed / 2" or 3" discharge, Banjo® sweep   |                             |
| ELECTRICAL                                       | 7-pole RV plug                               |                             |
| DOT ROAD LIGHTS                                  | Optional (clearance / stop / turn / tail)    |                             |

## — STANDARD EQUIPMENT

- Two cone-bottom poly tanks with Ribbed-Wall™ construction
- Hand-pump hydraulic lift – tow empty, lower to fill, raise to relocate
- Powder-coated 6"×2" tube frame with integrated hose-storage brackets
- Banjo® centrifugal poly pump on Honda® power
- Pump positioned for complete hose drainage
- 7-pole RV plug; four positive tie-down points

## — CONFIGURE / ADD

- 2" or 3" pump, fittings and discharge hose to match your flow
- Honda® GX160 (5.5 HP) or GX200 (6.5 HP) engine
- DOT-compliant LED road-light package for public-road travel
- Custom plumbing & manifold configurations
- Suited to water, fertilizer and a range of process liquids

BUILT TO YOUR SPEC | QUOTED WITH DRAWINGS

## REQUEST A QUOTE

Tell us your liquid, capacity and where it's headed. One Clarion configures the right build and stays your single point of contact from quote through delivery.

**863-261-8388**

info@oneclarion.com  
oneclarion.com