

# 525 GALLON SIMPSON WATER TRAILER

Built for demanding field use, the Simpson Water Trailer delivers dependable mobile water supply for dust control, washdown, irrigation support, and jobsite response.



*\*Images shown may include optional features. Actual product appearance may vary based on selected configurations.*

When water access is limited, productivity drops fast. The Simpson 525 Gallon Water Trailer gives contractors, growers, and municipal crews a durable, road-ready solution for moving water where fixed access is not available. This trailer is designed to support daily field use across construction sites, remote properties, maintenance routes, and emergency-response needs.

## Standard Features

- 525-gallon elliptical low-profile tank
- 158 GPM performance
- CRX® 210 engine with low-oil shutdown
- 2" semi-trash pump
- Hydrant fill and manifold discharge system
- Dual rear spray heads with flow control valves
- 20' suction hose and 50' discharge hose
- NATM-approved trailer

## Specifications

<b>Tank</b>	525-gallon low-profile polyethylene tank with 16" manhole, 4" vent, and sump pump
<b>Pump &amp; Engine</b>	CRX® 210, 208cc   2" semi-trash pump   low-oil shutdown
<b>Performance</b>	158 GPM   25' suction head lift
<b>Plumbing &amp; Hoses</b>	Hydrant fill, dual rear spray heads, garden hose connector, manifold discharge, flow control valves, 20' suction hose, 50' discharge hose
<b>Trailer</b>	NATM Certified   6" C-channel   13' overall length   13" axle clearance
<b>Running Gear</b>	Dual 5,200 lb axles   dual-leaf spring suspension   ST225-75R15 tires
<b>Utility Features</b>	5000 lb crank jack   adjustable height hitch   LED lighting   safety chains   rear storage basket
<b>Brakes</b>	Hydraulic (SWT525172HSB) or electric (SWT525172EB), depending on selected configuration
<b>Dim. &amp; Weight</b>	153" x 87" x 84"   Dry Weight 2500 lbs.   7000 lbs. GVW
<b>Warranty</b>	1-year frame   5-year pump   3-year engine
<b>Fuel Capacity</b>	0.8 gal.

## Special Features

- **3/8" thick polyethylene tank construction**  
Built for repeated field use with a durable low-profile design.
- **16" manhole with 4" vent and sump pump**  
Improves tank access and simplifies filling and maintenance.
- **6" C-channel trailer frame**  
Adds structural strength for demanding towing conditions.
- **13" under-clearance at axle**  
Improves ground clearance for rougher site conditions.
- **Dual-leaf spring suspension**  
Supports stability and durability across changing terrain.
- **5000 lb side-mount crank jack**  
Helps simplify positioning and hookup in the field.
- **LED lighting and safety chains with snap hooks**  
Adds practical towing and jobsite utility.
- **Large rear storage basket**  
Keeps accessories and field equipment organized and accessible.
- **Adjustable height hitch**  
Improves towing flexibility across different vehicles and setups.

## Options

Available configurations let you match the trailer to your towing setup and field requirements. Hitch options include 2" ball coupler, 2-5/16" ball coupler, or pintle-eye hitch, with an available fire hose reel kit for added deployment flexibility. Brake type varies by selected configuration.


**\*\*Specifications and available options may vary by selected configuration. Contact us to confirm the best setup for your tow vehicle, field conditions, and application.\*\***



*This product is 49-State/EPA-Compliant. Not for sale in the state of California.*

**863-261-8388**

**SCAN TO  
REQUEST CAD  
DRAWINGS OR  
SPECS:**



info@oneclarion.com  
www.oneclarion.com