

ONE CLARION · INDUSTRIAL WATER TRANSPORT

# 525 GALLON SIMPSON WATER TRAILER

525-gallon tandem-axle water trailer CRX 210 power, a 158 GPM semi-trash pump, and your choice of hydraulic or electric brakes. Built for municipal, fire, and construction fleets.



*\*Images shown may include optional features. Actual product appearance may vary based on selected configurations.*

<b>525<sup>GAL</sup></b> TANK CAPACITY	<b>158<sup>GPM</sup></b> MAX PUMP FLOW	<b>7,000<sup>LB</sup></b> GVW · TANDEM AXLE	<b>CRX 210</b> SIMPSON ENGINE	<b>NATM</b> APPROVED BUILD
-------------------------------------------	-------------------------------------------	------------------------------------------------	----------------------------------	-------------------------------

**CONFIGURE IT** | Choose hydraulic surge or electric brakes, your coupler type, and an optional fire-hose reel kit – one platform, configured to your fleet and your job.

## WHY CREWS CHOOSE IT

- CRX 210 POWER**  
 Simpson CRX 210 engine drives a 2" semi-trash pump at up to 158 GPM.
- DUAL SPRAY-HEAD MANIFOLD**  
 Twin rear spray heads for dust control, road prep, and broad-area wetting.
- TANDEM-AXLE NATM BUILD**  
 Dual-leaf spring suspension, 6" C-channel frame, 13" under-axle clearance.
- HYDRAULIC OR ELECTRIC BRAKES**  
 Match the brake system to your tow vehicle and fleet standard.
- COMPLETE HOSE PACKAGE**  
 2½"×25' hydrant fill, 20' suction, and 50' discharge hoses included.
- FIRE-SUPPRESSION READY**  
 Optional reel kit adds 50' of 1" fire hose with nozzle for emergency support.

## WHERE CREWS USE IT

- MUNICIPAL & PUBLIC WORKS
- CONSTRUCTION SITES
- DUST & ALLERGEN CONTROL
- FIRE SUPPRESSION SUPPORT
- RESORT & PROPERTY CARE
- EMERGENCY RESPONSE

# SIMPSON SWT525 – SPECIFICATIONS & CONFIGURATION

## BUILD CONFIGURATIONS

OPTION	CHOICES
<b>BRAKE SYSTEM</b>	Hydraulic surge   Electric
<b>COUPLER</b>	2" ball   2-5/16" ball   Pintle-eye hitch
<b>FIRE HOSE REEL KIT</b>	Optional – 50' × 1" rubber hose, nozzle & mounting hardware

## SPECIFICATIONS

CHASSIS & RUNNING GEAR		PUMP & PLUMBING	
Configuration	Tandem axle	Engine	Simpson CRX 210
Suspension	Dual-leaf spring	Pump	2" semi-trash
Frame	6" C-channel	Max flow	Up to 158 GPM
GVW	7,000 lb	Manifold	Dual spray-head
Brakes	Hydraulic surge or electric	Hydrant fill hose	2½" × 25'
Jack	5,000 lb side-mount crank	Suction hose	20'
Hitch	Adjustable height	Discharge hose	50'
Safety	(2) chains with snap hooks	Tank capacity	525 gallons
Lighting	LED	Optional	Fire hose reel kit (50' × 1")
Clearance	13" under-axle		
Compliance	NATM-approved		



## WARRANTY

**1 YR**  
FRAME

**5 YR**  
PUMP

**3 YR**  
ENGINE

**COMPLIANCE NOTICE:** This unit is 49-state EPA-compliant and is **NOT AVAILABLE FOR SALE IN CALIFORNIA**. Contact us for California-compliant alternatives.

## READY TO ROLL?

Tell us your brake, coupler, and kit configuration – we'll quote your SWT525.

**REQUEST A QUOTE**

Product illustration is representative. Specifications and included equipment are approximate, vary by configuration, and are provided for reference only. Confirm final build details at time of quote.